



## Features & Benefits

Commercial Medium Body signs have hingeable frames that allows access to service the sign. The frames have provisions for Tension Clips, Corner Angles, Frame Braces and Corner Keys. It is available in two finish options. (Mill finish and Dark Quaker Bronze.) The face material does not need to be hemmed and will not require grommets or double faced tape.

## Answers to FAQ's

- Accepts up to 22 oz banner material.
- Tension Clip placement - Tension clips are to be placed approximately 1-1/2" in from the edge of the trimmed to size face material.
- Tension Clip spacing - Every 6" on center.
- Face material trim size - Add 1-1/2" to all four sides, from the outside dimension of the assembled frame. (Add a total of 3" of face material to both the height and width of the assembled frame.)
- Visible opening - Deduct 4-1/2" from the cabinet height and width.
- Add 1" in the direction of the lamp to allow for standard T12 bulbs to fit.
- Recommended lamp spacing every 10" on center.
- Frame Brace and Frame Support placement - Place every 36" on center horizontally and vertically.
- The Tension Tool that is required for this frame is Part #5135.

## Optional Items

- 6" Cast Radius Corner Part #4545
- 9" Cast Radius Corner Part #4540
- Dual Divider Part #2142 & 2-1/2" Dual Divider Cover Part # 2146.
- Raceway Cover Part #5114
- Socket Raceway & Cover - see Standard Product Catalog Page 12
- Frame Support Tube Part #2175

