



Features & Benefits

The Commercial Single Face Body has a hingeable frame that allows access to service the sign. The Tension Frame II was specifically engineered to help reduce shadows and is the best solution for white transparent or light colored backgrounds. The frame has provisions for Tension Clips, Corner Angles, Frame Braces and Corner Keys. The face material does not need to be hemmed and will not require grommets or double faced tape. It is available in Mill finish and Dark Bronze.

Answers to FAQ's

- Accepts up to 22 oz banner material
- Tension Clip placement - Tension clips are to be placed approximately 1-1/2" from the edge of the trimmed to size face material
- Tension Clip spacing - Every 5" on center
- Face material trim size - Add 3-1/4" to all four sides to the outside dimension of the assembled frame (Add a total of 6-1/2" of face material to both the height and width of the assembled frame)
- Frame Brace and Frame Support placement - Place every 36" on center horizontally and vertically
- When using standard T12 bulbs, add 1" to the direction of the lamps
- Recommended lamp spacing every 12" on center
- 2 Piece Frame Brace, part #5357 should be used when using LED's
- The Tension Tool that is required for this frame is Part #5135

Optional Items

- Frame Support Tube, Part #2175
- 2 Piece Frame Brace, Part #5357
- Socket Raceway & Cover
- Tension Tool, Part #5135
- Raceway Cover, Part #5112

